## ASSEMBLY INSTRUCTION SH278KBGE-1 & SH278KGRY-1 & SH278KDGR-1

1 Headboard	2 Headboard Leg (R)	3 Headboard Leg (L)	4 Footboard	5 Footboard Leg
Barris	• • • • • • • • • • • • • • • • • • •	· · · · · · · · · · · · · · · · · · ·		°
x1	x1	x1	×1	x2
6 Side Rail (L)	7 Side Rail (R)	8 Side Rail Support Leg	9 Slat	<b>10</b> Support Leg with adjustable feet
	. Ca			
x2	x2	x2	x4	x12
A Bolts	B Bolts	C Bolts	<b>D</b> Bolts	E Bolts
M8 x 20mm	M8 x 50mm	M6 x 25mm	M6 x 40mm	M6 x 70mm
		())	(d)	()
x8	x4	x8	x12	x2
F Wood	G Lock Washer	H Flat Washer	Lock Washer	J Flat Washer
Dowel	M8 x 14mm	M8 x 22mm	M6 x 13mm	M6 x 19mm
	(		$\bigcirc$	(0)
x2	x4	x4	x8	x8
		K Screw M4 x 32mm	L Allen Key M5 x 65mm	M Allen Key M4 x 65mm
		x8	x1	x1

This page lists all the contents included in the box. Please take the time to identify the hardware as well as the individual components to this product. As you unpack and prepare for assembly, place the contents on a carpeted or padded area to protect them from damage.


## ASSEMBLY INSTRUCTION SH278KBGE-1 & SH278KGRY-1 & SH278KDGR-1

Begin assembly by attaching each Headboard Leg (2) & (3) to the bottom of the Headboard (1) by aligning the hole and securing with 2 Allen Bolts (B), 2 Lock Washer (G), 2 Flat Washer (H) per leg using Allen Key (L). (DO NOT FULLY TIGHTEN BOLTS FOR THIS STEP)

 1
 BACK


 1
 BACK

Attach Side Rail Support Leg (8) to the join of the Side Rail (6) and Side Rail (7) by securing with 4 Allen Bolts (C), 4 Lock Washer (I), 4 Flat washer (J) per support using Allen Key (M).




until assembly is complete and the bed is level.

5 Attach Support Legs (10) to Slat (9) by securing with 1 Allen Bolt (D) per support leg. Attach Slat (9) to Side Rail by securing with 1 Screw (K) each side. Tighten all screws using philips head screw driver (NOT INCLUDED). Tighten all bolts using Allen Key (L) & (M).




Attach each Footboard Legs (5) to the bottom of the Footboard (4) by inserting a Dowel (F) & securing with 1 Allen Bolt (E) per leg using Allen Key (M).



4 Attach Side Rail to the Headboard Leg (2) & (3) and Footboard (4). Aligning holes , and securing with 2 Allen Bolts (A) each and using Allen Key (L).

(DO NOT FULLY TIGHTEN BOLTS FOR THIS STEP) \*Attach bolts to Headboard Leg & Footboard first , follow by slot in the Side Rail.



## Cleaning & Care

Treat surface with care. Surface is resistant to scratches but is not scratch resistant. Clean surfaces with a dry or damp soft cloth. Do not use abrasive cleaners. Hardware may loosen over time. Periodically check that all connections are tight.